

EVENT SITE MEASUREMENT

POLE VAULT

Rule Requirement		
Runway	Length	m
	Width	m
	It is marked by white lines 0.05m in width	<input type="checkbox"/> YES <input type="checkbox"/> NO
	There are marks beside the runway at each 0.5m between points 2.5m to 5m from the "0" line and at each 1m from 5m to 18m	<input type="checkbox"/> YES <input type="checkbox"/> NO
Inclination	The maximum lateral inclination of the runway is less than 1:100	<input type="checkbox"/> YES <input type="checkbox"/> NO
	In the last 40m of the runway, the overall downward inclination in the running direction is less than 1:1000	<input type="checkbox"/> YES <input type="checkbox"/> NO
Pole Vault box	Size, material and construction are in accordance with the rule	<input type="checkbox"/> YES <input type="checkbox"/> NO
Zero line	A white line, 0.01m wide, is drawn at right angles to the axis of the runway, in line with the top back end of the box	<input type="checkbox"/> YES <input type="checkbox"/> NO
Notes		

Runway Surface	
See list : https://www.worldathletics.org/about-iaaf/documents/technical-information	
Product name	
Product manufacturer	
Absolute thickness	
World Athletics Product Certificate number	

Event Site – Spot Levels

- Use the diagram to provide runway levels at the box and at 40m from each Pole Vault box.
- It is essential that reduced levels (not grades) be provided on each of the runways.
- The sign convention used by World Athletics for inclinations is that an upward inclination in the direction of running is positive.

Spot Levels – Pole Vault

Provide runway levels at the box (0.000m) and at 40m from each Pole Vault box.

